



APPLICATION and PERFORMANCE SPECIFICATION

ACT1S21RS120N

- Line Voltage: 120V 60Hz
- Rapid Start
- Lamp End of Life Protection

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD \leq %	PF \geq	CF \leq	BF	BEF
Type	No.	Watts									
* F21T5	1	21	0/-18	120	0.33	21	130	0.5	1.7	0.80	3.80
F14T5	1	14	0/-18	120	0.26	16	140	0.5	1.7	0.95	5.90
F13T5	1	13	0/-18	120	0.26	16	140	0.5	1.7	1.00	6.00

Note: Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C62.41-2002
- Meets FCC 18 CONSUMER Limits

Safety

- No PCB's
- UL & cUL listed (Class P, Type 1 Outdoor)
- 0CV 300V

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C
- Starting time: 0.5s < t < 2s

Physical Parameters

- Length 5.9" (150mm)
- Width 0.9" (23.7mm)
- Height 0.75" (19.1mm)
- Weight 0.29lbs

Lead Length

- White/Black 12" \pm 1"
- Blue 31" \pm 1"
- Red 19" \pm 1"

