



APPLICATION and PERFORMANCE SPECIFICATION

ACT2S70PSUNV

- Line Voltage:120-277V 50/60Hz
- Series Lamp Operation
- Type CC
- Program Start
- Active Power Factor Correction

Lamp Type			Min. Start Temp. (°F °C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF
Type	No.	Watts									
* F70T8	2	70	-22/-30	120	1.16	139	10	0.99	1.7	0.95	0.68
F58T8	2	58	-22/-30	120	1.08	129	10	0.99	1.7	1.07	0.83
* F70T8	2	70	-22/-30	277	0.5	135	10	0.96	1.7	0.95	0.70
F58T8	2	58	-22/-30	277	0.47	126	10	0.96	1.7	1.07	0.85
F36T8	2	36	-22/-30	120	0.89	107	10	0.99	1.7	1.5	1.4
F36T8	2	36	-22/-30	277	0.39	105	10	0.97	1.7	1.5	1.4
F70T8	1	70	-22/-30	120	0.62	74	10	0.99	1.7	1.08	1.46
F58T8	1	58	-22/-30	120	0.55	66	10	0.99	1.7	1.17	1.79
F70T8	1	70	-22/-30	277	0.28	73	10	0.92	1.7	1.08	1.46
F58T8	1	58	-22/-30	277	0.26	65	10	0.90	1.7	1.17	1.79

Note: the above data is tested at 60Hz.

Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C82.11-2002
- Meets ANSI Standard C62.41-2002
- Meets FCC 18 Non CONSUMER Limits

Application

- Maximum Ambient Temperature: 131°F,55°C
- Remote Mounting: 6 ft. max. Lead length, 18AWG
- Sound Rated: A
- Maximum case temperature Tc: 194°F,90°C

Safety

- No PCB's, Type HL
- UL & cUL listed (Class P, Type 1 Outdoor)
- OCV 300V

Physical Parameters

- Length * Width * Height 9.75 " *1.6 " *1.1 "
- Mounting 8.9"
- Weight 1.10 lbs
- White, Black 25"(±1")
- Orange 20"(±1")
- Brown 20"(±1")
- Yellow 20"(±1")
- Red/ Blue 20"(±1")

